




4-Port PS/2 KVM Switch

CS64A KVM Switch has a handy design integrating with 6 feet of cables.
It can control 4 servers via a single console.

Setup



Features

- One PS/2 console controls four PS/2 computers
- Compact design, built-in 1.8 m (6 feet) cables
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered

Specifications

Function			CS64A
Computer Connections			4
Port Selection			Hotkeys
Connectors	Console Ports	Keyboard	1 x 6-pin Mini-DIN Female (Purple)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x 6-pin Mini-DIN Female (Green)
		Speaker	1 x Mini Stereo Jack Female (Green)
	KVM Ports	Keyboard	4 x 6-pin Mini-DIN Male (Purple)
		Video	4 x HDB-15 Male (Blue)
		Mouse	4 x 6-pin Mini-DIN Male (Green)
		Speaker	4 x Mini Stereo Plug Male (Green)
LEDs	Selected	4 x Green	
Cable Length	Computers	1.8m	
Emulation	Keyboard/Mouse	PS/2	
Video Resolution			2048 x 1536; DDC2B
Scan Interval			5 Seconds
Environment	Operating Temp	0-50°C	
	Storage Temp	-20-60°C	
	Humidity	0-80% RH Non-condensing	
Physical Properties	Housing	Plastic	
	Weight	0.83 kg	
	Dimensions (L x W x H)	8.95 x 7.19 x 2.60 cm	

* The specifications and pictures are subject to change without notice.