CL1008/1016

Slideaway™ LCD KVM Switch

The CL1008 / CL1016 LCD KVM Switch series are control units that allow access to multiple computers from a single keyboard, video, and mouse (KVM), console. A single CL1008 or CL1016 can control up to 8 or 16 computers. As many as 15 additional KVM switches can be daisy-chained to the CL1008 / CL1016, so that up to 256 computers can all be controlled from a single KVM console.

The CL1008 / CL1016 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" LCD monitor, and touchpad in a 1U rack-mountable sliding housing.

Setup



Features

- KVM console with 17" LCD monitor in a sliding housing with top and bottom clearance for smooth operation in a 1U high system rack
- LCD module rotates up to 115 degrees for a more comfortable viewing angle
- Standard rack mount kit included – optional Easy Rack Mounting (single person installation) rack mount kit available (requires separate purchase)
- Daisy-chain up to 15 additional units – control up to 256 computers
- No software required – convenient computer selection via hotkeys and mouse driven intuitive on screen display (OSD) menus
- Auto Scan feature for monitoring user-selected computers
- Broadcast support – commands from the keyboard can be broadcast to all available computers on the installation
- Hot pluggable – add or remove computers without having to power down the switch
- Two level password security – only authorized users view and control the computers; up to four users plus an administrator with separate profiles for each
- Video settings of attached computers are automatically adjusted for optimal output to the LCD monitor
- Upgradable firmware
- Keyboard Language support: English(US); English(UK); German; German(Swiss); French; Spanish; Traditional Chinese; Japanese; Korean; Swedish; Italian; Russian; Hungarian

Rack Mount Kit	Depth (cm)
Long (Optional)	68 - 105
Short (Standard)	42 - 82

Easy Installation Rack Mount Kit	Depth (cm)
Long (Optional)	68 - 105
Short (Optional)	52 - 70

Specifications

Function			CL1008	CL1016
Computer Connections	Direct		8	16
	Max		128 (via Daisy-chain)	256 (via Daisy-chain)
Port Selection			OSD; Hotkey; Pushbutton	
Connectors	KVM Ports		8 x SPHD Female (Yellow)	16 x SPHD Female (Yellow)
	Daisy-Chain		1 x DB-25 Male	
	FW Upgrade		1 x RJ-11 Female	
	Power		1 x 3-prong AC socket	
Switches	Reset		1 x Semi-recessed pushbutton	
	Power		1 x Rocker	
	F/W Upgrade		1 x Slide	
	LCD Adjust		4 x Pushbutton	
	Port Selection		8 x Pushbutton	16 x Pushbutton
LEDs	On Line		8 (Orange)	16 (Orange)
	Selected		8 (Green)	16 (Green)
	Power		1 (Dark Green)	
	Lock	Num	1 (Green)	
		Caps	1 (Green)	
		Scroll	1 (Green)	
Emulation	Keyboard / Mouse		PS/2	
Video		17" LCD	1280 x 1024 @ 75 Hz; DDC2B	
Scan Interval (OSD Select)			1-255 Seconds	
I/P Rating			100-240V AC; 50/60Hz; 1A	
Power Consumption		17" LCD	120V; 30W 230V; 37W	
Environment	Operating Temp.		0-40°C	
	Storage Temp.		-20-60°C	
	Humidity		0-80% RH-condensing	
Physical Properties	Housing		Metal+Plastic	
	Weight	17" LCD	13.10 kg	13.30kg
	Dimensions (D x W x H)		63.40 x 48.00 x 4.40 cm (19"/1U)	

* The specifications and pictures are subject to change without notice.

www.aten.com

Headquarters
ATEN International Co., Ltd.
3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Tel: 886-2-8692-6789 Fax: 886-2-8692-6767 E-mail : online@aten.com.tw

© Copyright 2011 ATEN® International Co., Ltd. All brand names and trademarks are the registered property of their respective owners.

2011. Version 4.0